

Portable solutions A solution intended for the sector operating in the area of securing the perimeter of sites and premises for the time of construction, renovation, demolition, etc. Considered to be the most important access control elements, the gates were fitted with steel bases and concrete ballast that stabilize the entire structure without the need to prepare foundations or install anchors. **TRAFFIC** V-KING **INDUSTRIAL FENCES**

10 m

20 m

V-KING gates

The V-King folding gates are dedicated for industries where quick, heavy duty, reliable, and safe operation is needed. This solution is perfect for logistics centres, ports, airports, and other industrial areas.

The V-King combines the advantages of a double-leaf gate and a barrier, enabling permanent access control or traffic control.

Special features

Reliable - top priority ever since the design concept stage. The structure, as well as the selection of accessories and the drive unit were all taken into consideration with a view to ensuring the highest reliability.

Safety. 10 safety edges come as standard. With emphasis on safety, the gate was fitted with systems preventing situations where property, e.g. a passing vehicle, could be damaged or a person could be injured.

High-speed - adjustable operating speed from 1 m/s, indispensable when a high level of perimeter protection is needed at sites with a high traffic volume. Moreover, drive units with the best reliability factor are used.

Heavy duty operation. The reinforced structure of the gate is designed for continuous operation.



Safety of use

of this ultramodern and high-speed gate is ensured by numerous safety systems. The standard accessories include 2 photocell kits, 10 safety edges, two emergency stops, and a LED warning light. The gates can be fitted with auxiliary infrared barriers and light barriers. All this to make sure that the gate can operate without additional supervision in high-volume vehicle or pedestrian traffic.

The V-King gate is available in a single-leaf and a double-leaf version. The gate can close off opening widths up to 10 [m] wide and 2.5 [m] high.


Confidence confirmed with a 5-year warranty for the complete product.





V-KING gates

Infill types




25x25 section infill




Section infill 25x25 [mm] in the Caro arrangement (welded to the structure)






VEGA B mesh panel infill (screwed to the structure)



Profile infill 30x18 [mm] (welded to the structure)



Round tube section infill 25 [mm] (welded to the structure)



AW.10.77 Infill. Round hollow section infill with a diameter of Ø 25

V-KING gates

Automation solutions

Drive units with an oil bath gear are dedicated for heavy duty operation and are characterized by reliability and smooth operation – adjustable opening speed from 1 m/s. The reliability of the drive unit was proven by field tests.

500 000 cycle warranty.



